

Package: vayr (via r-universe)

May 15, 2026

Title Extensions for 'ggplot2' to Visualize as You Randomize

Version 1.0.0

Description Position adjustments for 'ggplot2' to implement ``visualize as you randomize'' principles, which can be especially useful when plotting experimental data.

License GPL-2 | file LICENSE

URL <https://alexandercoppock.com/vayr/index.html>

Depends R (>= 4.1.0)

Imports ggplot2 (>= 3.0.0), packcircles (>= 0.3.7), withr (>= 2.1.1)

Suggests dplyr, estimatr, knitr, patchwork, randomizr, rmarkdown, sessioninfo, testthat, tibble, tidyverse

VignetteBuilder knitr

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

Repository <https://acoppock.r-universe.dev>

Date/Publication 2025-04-10 18:03:52 UTC

RemoteUrl <https://github.com/acoppock/vayr>

RemoteRef HEAD

RemoteSha aa5e3d320081507da42b6eb1041ae8aa9270145d

Contents

patriot_act	2
position_circlepack	2
position_circlepackdodge	4
position_jitter_ellipse	5
position_jitterdodge_ellipse	6
position_sunflower	7

position_sunflowerdodge	8
sunflower	9
vayr	11

Index	12
--------------	-----------

patriot_act	<i>Original and Replication data for the Patriot Act experiment described in Persuasion in Parallel</i>
-------------	---

Description

Original and Replication data for the Patriot Act experiment described in Persuasion in Parallel

Usage

```
patriot_act
```

Format

patriot_act:

A data frame with 2062 rows and 4 columns:

sample_label The original study (Chong and Druckman (2011) or the Mechanical Turk replication)

pid_3 Subject partisanship (limited to Republicans and Democrats, including leaners)

T1_content Content of assigned treatment condition: pro-Patriot act statements, anti-Patriot act statements, or a control

PA_support Post-treatment support for the Patriot Act on a 1 to 7 Likert scale

Source

[doi:10.7910/DVN/I9GSKI](https://doi.org/10.7910/DVN/I9GSKI)

position_circlepack	<i>Arrange over-plotted points with a circle-packing algorithm</i>
---------------------	--

Description

This function uses a circle packing algorithm from the 'packcircles' package to arrange perfectly over-plotted points of varying sizes into an elliptical area.

Usage

```
position_circlepack(density = 1, aspect_ratio = 1)
```

Arguments

density	The density of the circle pack, which defaults to 1 but will have to be adjusted in most cases. The desirable density will depend on both the ranges of the axes and the dimensions of the image. It will also depend on the size scale.
aspect_ratio	An aspect ratio adjustment to compensate for distortion of the circular arrangement, which might occur when plotting if <code>coord_equal()</code> is not used. A wide aspect ratio (eg. 2) would adjust for vertical stretching, whereas a tall aspect ratio (eg. 0.5) would adjust for horizontal stretching. The default aspect ratio of 1 is appropriate when no adjustment is required.

Value

A ggproto object of class `PositionCirclePack`.

See Also

Other Functions: [position_circlepackdodge\(\)](#), [position_jitter_ellipse\(\)](#), [position_jitterdodge_ellipse\(\)](#), [position_sunflower\(\)](#), [position_sunflowerdodge\(\)](#), [sunflower\(\)](#)

Examples

```
library(ggplot2)
library(dplyr)
library(randomizr)
library(tibble)

dat <- data.frame(
  X = c(rep(0, 200)),
  Y = rep(0, 200),
  size = runif(200, 0, 1)
)

ggplot(dat, aes(x = X, y = Y, size = size)) +
  geom_point(position = position_circlepack(density = 0.25, aspect_ratio = 1),
            alpha = 0.25) +
  coord_equal(xlim = c(-1, 1), ylim = c(-1, 1), expand = TRUE) +
  theme(legend.position = "none")

# Applied to a mock experiment with weighted groups

dat <-
  tibble(
    age_group = rep(c("young", "middle", "old"), c(100, 200, 300)),
    treatment = block_ra(age_group, block_m = c(50, 50, 50)),
    latent_outcome =
      case_when(age_group == "young" & treatment == 0 ~ 0.10,
                age_group == "young" & treatment == 1 ~ 0.20,
                age_group == "middle" & treatment == 0 ~ 0.40,
                age_group == "middle" & treatment == 1 ~ 0.45,
                age_group == "old" & treatment == 0 ~ 0.70,
                age_group == "old" & treatment == 1 ~ 0.90),
  )
```

```

      outcome = rbinom(600, size = 1,
                      prob = latent_outcome)
    )

  dat <-
  dat |>
  mutate(
    treatment_prob =
      case_when(age_group == "young" ~ 50/100,
                age_group == "middle" ~ 50/200,
                age_group == "old" ~ 50/300),
    weights = 1/case_when(treatment == 1 ~ treatment_prob,
                          treatment == 0 ~ 1 - treatment_prob)
  )

  ggplot(dat, aes(treatment, outcome, size = weights, color = age_group)) +
  geom_point(alpha = 0.5, position = position_circlepack(density = 0.5))

```

position_circlepackdodge

Arrange over-plotted points with a circle-packing algorithm and dodge groups side-to-side

Description

This function dodges groups and uses a circle packing algorithm from the 'packcircles' package to arrange perfectly over-plotted points of varying sizes into an elliptical area.

Usage

```
position_circlepackdodge(width = 1, density = 1, aspect_ratio = 1)
```

Arguments

width	The dodging width, which defaults to 1.
density	The density of the circle pack, which defaults to 1 but will have to be adjusted in most cases. The desirable density will depend on both the ranges of the axes and the dimensions of the image. It will also depend on the size scale.
aspect_ratio	An aspect ratio adjustment to compensate for distortion of the circular arrangement, which might occur when plotting if coord_equal() is not used. A wide aspect ratio (eg. 2) would adjust for vertical stretching, whereas a tall aspect ratio (eg. 0.5) would adjust for horizontal stretching. The default aspect ratio of 1 is appropriate when no adjustment is required.

Value

A ggproto object of class PositionCirclePackDodge.

See Also

Other Functions: [position_circlegpack\(\)](#), [position_jitter_ellipse\(\)](#), [position_jitterdodge_ellipse\(\)](#), [position_sunflower\(\)](#), [position_sunflowerdodge\(\)](#), [sunflower\(\)](#)

Examples

```
library(ggplot2)

dat <- data.frame(
  X = c(rep(0, 200)),
  Y = rep(0, 200),
  size = runif(200, 0, 1),
  id = (rep(c("A", "B"), 100))
)

ggplot(dat, aes(x = X, y = Y, size = size, color = id)) +
  geom_point(position = position_circlegpackdodge(width = 1, density = 1, aspect_ratio = 1),
            alpha = 0.25) +
  coord_equal(xlim = c(-1, 1), ylim = c(-1, 1), expand = TRUE) +
  scale_size_continuous(range = c(1, 3)) +
  theme(legend.position = "none")
```

position_jitter_ellipse

Jitter points on an ellipse to avoid over-plotting

Description

This function adds elliptical random noise to perfectly over-plotted points, offering a pleasing way to visualize many points that represent the same position. In contrast to the `position_jitter()` function which samples from a rectangular field, the `position_jitter_ellipse()` function samples from an elliptical field. This function takes algorithmic inspiration from <https://stackoverflow.com/questions/5529148/algorithm-calculate-pseudo-random-point-inside-an-ellipse> and <https://stats.stackexchange.com/questions/120527/simulate-a-uniform-distribution-on-a-disc>.

Usage

```
position_jitter_ellipse(width = NULL, height = NULL, seed = NA)
```

Arguments

width, height	The dimensions of the elliptical field, from which over-plotted points are sampled.
seed	A random seed for reproducibility.

Value

A ggproto object of class `PositionJitterEllipse`.

See Also

Other Functions: [position_circlepack\(\)](#), [position_circlepackdodge\(\)](#), [position_jitterdodge_ellipse\(\)](#), [position_sunflower\(\)](#), [position_sunflowerdodge\(\)](#), [sunflower\(\)](#)

Examples

```
library(ggplot2)

dat <- data.frame(x = rep(1, 500), y = rep(1, 500))

# Jitter on an ellipse.
ggplot(dat, aes(x, y)) +
  geom_point(position = position_jitter_ellipse(width = 0.5, height = 0.5)) +
  coord_cartesian(xlim = c(0, 2), ylim = c(0, 2))

# Jitter on a rectangle, for comparison.
ggplot(dat, aes(x, y)) +
  geom_point(position = position_jitter(width = 0.5, height = 0.5)) +
  coord_cartesian(xlim = c(0, 2), ylim = c(0, 2))
```

position_jitterdodge_ellipse

Jitter points on an ellipse and dodge groups side-to-side

Description

This function dodges groups of points side-to-side and adds elliptical random noise to perfectly over-plotted points. See the [position_jitter_ellipse\(\)](#) documentation for more information.

Usage

```
position_jitterdodge_ellipse(
  jitter.width = NULL,
  jitter.height = NULL,
  dodge.width = 1,
  seed = NA
)
```

Arguments

jitter.width, jitter.height	The dimensions of the elliptical field, from which over-plotted points are sampled.
dodge.width	The dodging width, which defaults to 1.
seed	A random seed for reproducibility.

Value

A ggproto object of class PositionJitterdodgeEllipse.

See Also

Other Functions: [position_circlepack\(\)](#), [position_circlepackdodge\(\)](#), [position_jitter_ellipse\(\)](#), [position_sunflower\(\)](#), [position_sunflowerdodge\(\)](#), [sunflower\(\)](#)

Examples

```
library(ggplot2)

dat <- data.frame(x = rep(1, 500), y = rep(1, 500),
                 group = sample(LETTERS[1:2], 500, replace = TRUE))

ggplot(dat, aes(x, y, shape = group, color = group)) +
  geom_point(position = position_jitterdodge_ellipse(jitter.width = 0.5,
                                                    jitter.height = 0.5,
                                                    dodge.width = 1)) +
  coord_cartesian(xlim = c(0, 2), ylim = c(0, 2))
```

position_sunflower *Arrange over-plotted points in a sunflower pattern*

Description

This function applies the sunflower algorithm, executed by the `sunflower()` function, as a position adjustment, arranging overlapping points at any given x and y into a sunflower pattern. See the `sunflower()` documentation for more information.

Usage

```
position_sunflower(density = 1, aspect_ratio = 1)
```

Arguments

density	The pattern density, which defaults to 1 but will have to be adjusted in most cases. The desirable density will depend on both the ranges of the axes and the dimensions of the image.
aspect_ratio	An aspect ratio adjustment to compensate for distortion of the circular arrangement, which might occur when plotting if <code>coord_equal()</code> is not used. A wide aspect ratio (eg. 2) would adjust for vertical stretching, whereas a tall aspect ratio (eg. 0.5) would adjust for horizontal stretching. The default aspect ratio of 1 is appropriate when no adjustment is required.

Value

A ggproto object of class PositionSunflower.

See Also

Other Functions: [position_circlepack\(\)](#), [position_circlepackdodge\(\)](#), [position_jitter_ellipse\(\)](#), [position_jitterdodge_ellipse\(\)](#), [position_sunflowerdodge\(\)](#), [sunflower\(\)](#)

Examples

```
library(ggplot2)

# Use the sunflower position function to arrange N points
N <- 100

dat <- data.frame(
  x = rep(1:4, times = N),
  y = rep(1:4, times = N)
)

ggplot(dat, aes(x = x, y = y)) +
  geom_point(size = 1, position = position_sunflower(density = 1, aspect_ratio = 1)) +
  xlim(0, 5) +
  ylim(0, 5) +
  coord_equal()
```

position_sunflowerdodge

Arrange over-plotted points in a sunflower pattern and dodge groups side-to-side

Description

This function applies the sunflower position adjustment alongside the dodge position adjustment, arranging overlapping points per x, y, and group into a sunflower pattern. See the [sunflower\(\)](#) documentation for more information.

Usage

```
position_sunflowerdodge(width = 1, density = 1, aspect_ratio = 1)
```

Arguments

width	The dodging width, which defaults to 1.
density	The pattern density, which defaults to 1 but will have to be adjusted in most cases. The desirable density will depend on both the ranges of the axes and the dimensions of the image.
aspect_ratio	An aspect ratio adjustment to compensate for distortion of the circular arrangement, which might occur when plotting if <code>coord_equal()</code> is not used. A wide aspect ratio (eg. 2) would adjust for vertical stretching, whereas a tall aspect ratio (eg. 0.5) would adjust for horizontal stretching. The default aspect ratio of 1 is appropriate when no adjustment is required.

Value

A ggproto object of class `PositionSunflowerDodge`.

See Also

Other Functions: [position_circlepack\(\)](#), [position_circlepackdodge\(\)](#), [position_jitter_ellipse\(\)](#), [position_jitterdodge_ellipse\(\)](#), [position_sunflower\(\)](#), [sunflower\(\)](#)

Examples

```
library(ggplot2)

# Use the sunflower dodge position function to arrange and dodge N points.
N <- 300

dat <- data.frame(
  x = sample(1:2, size = N, replace = TRUE),
  y = sample(1:7, size = N, replace = TRUE),
  type = factor(sample(LETTERS[1:2], N, replace = TRUE))
)

# With coord_equal
ggplot(dat, aes(x, y, color = type, shape = type)) +
  geom_point(position = position_sunflowerdodge(width = 0.5, density = 2, aspect_ratio = 1)) +
  coord_equal()

# Without coord_equal, might want to play with aspect ratio to get a pleasing plot
ggplot(dat, aes(x, y, color = type, shape = type)) +
  geom_point(position = position_sunflowerdodge(width = 0.5, density = 10, aspect_ratio = 1/4))
```

sunflower

Distribute points using a sunflower seed algorithm

Description

This function distributes points in an ellipse via a sunflower seed algorithm as a solution for overplotting. To implement the algorithm, this function adapts the code from <https://stackoverflow.com/questions/28567166/uniformly-distribute-x-points-inside-a-circle>.

Usage

```
sunflower(x = NULL, y = NULL, density, aspect_ratio)
```

Arguments

<code>x, y</code>	The identical coordinates of multiple over-plotted points, as vectors, which will be arranged using a sunflower seed algorithm.
<code>density</code>	The pattern density.
<code>aspect_ratio</code>	An aspect ratio adjustment to compensate for distortion of the circular arrangement, which might occur when plotting if <code>coord_equal()</code> is not used. A wide aspect ratio (eg. 2) would adjust for vertical stretching, whereas a tall aspect ratio (eg. 0.5) would adjust for horizontal stretching. An aspect ratio of 1 is appropriate when no adjustment is required.

Value

A numeric vector of adjusted x or y positions, computed using a sunflower seed algorithm.

See Also

Other Functions: [position_circlepack\(\)](#), [position_circlepackdodge\(\)](#), [position_jitter_ellipse\(\)](#), [position_jitterdodge_ellipse\(\)](#), [position_sunflower\(\)](#), [position_sunflowerdodge\(\)](#)

Examples

```
library(ggplot2)
library(dplyr)

# Manually adjust position of N points,
# arranging them per the sunflower algorithm and then dodging groups
N <- 300

dat <- data.frame(
  x = sample(1:2, size = N, replace = TRUE),
  y = sample(1:7, size = N, replace = TRUE),
  type = factor(sample(LETTERS[1:2], N, replace = TRUE))
) |>
  group_by(x, y, type) |>
  mutate(
    x = sunflower(x = x, density = 1, aspect_ratio = 1),
    y = sunflower(y = y, density = 1, aspect_ratio = 1),
    x = if_else(type == "A", x - (1 / 8), x + (1 / 8))
  )

ggplot(dat, aes(x, y, color = type, shape = type)) +
  geom_point() + coord_equal()
```

Description

Position adjustments for 'ggplot2' to implement "visualize as you randomize" principles, which can be especially useful when plotting experimental data.

Details

The 'vayr' package provides 'ggplot2' extensions that foster "visualize as you randomize" principles. These principles should guide the visualization of experimental data. Thus far, the package includes position adjustments to avoid over-plotting, facilitating plotting in "data-space." The 'vayr' paper is here: https://alexandercoppock.com/coppock_2020.pdf.

Author(s)

Maintainer: Alexander Coppock <acoppock@gmail.com> ([ORCID](#)) [copyright holder]

Other contributors:

- Elias Hyde <eliasworrallhyde@gmail.com> [contributor]

See Also

Useful links:

- <https://alexandercoppock.com/vayr/index.html>

Index

* **Data**

patriot_act, 2

* **Functions**

position_circlepack, 2

position_circlepackdodge, 4

position_jitter_ellipse, 5

position_jitterdodge_ellipse, 6

position_sunflower, 7

position_sunflowerdodge, 8

sunflower, 9

* **Package**

vayr, 11

* **datasets**

patriot_act, 2

patriot_act, 2

position_circlepack, 2, 5–10

position_circlepackdodge, 3, 4, 6–10

position_jitter_ellipse, 3, 5, 5, 7–10

position_jitterdodge_ellipse, 3, 5, 6, 6,
8–10

position_sunflower, 3, 5, 6, 7, 7, 9, 10

position_sunflowerdodge, 3, 5–7, 8, 8, 10

sunflower, 3, 5–8, 9, 9

vayr, 11

vayr-package (vayr), 11